

Anti-Curling Display Film

PRODUCT: FF-330

FEATURES / APPLICATIONS:

- Perfect product with non-curling at the edge and lay-flat appearance
- Super smooth surface makes it perfect for high-resolution printing and grey back for good opacity
- Ideal choice for X displays, roll-up displays, window shop advertising, posters, hanging and decorations
- Compatible with Solvent, Eco-solvent, UV inks and screen printing, no lamination required

MATERIAL DETAILS

PROPERTIES	TEST METHOD	METRIC	IMPERIAL
Average Weight	/	330g/sq.m	9.7oz/sq.yd
Product Structure	/	70mic white PVC+ 70mic white PVC +75mic PET	
Film Thickness	/	0.24-0.25mm	9.45-9.84mil
Available Width	/	0.914/1.07/1.27/1.37/1.52m	36"/42"/50"/54"/60"
Regular Length	/	30/50m	33/55yds

INK PRINTABILITY

Solvent	Eco Solvent	UV	Latex
☐	☐	☐	
Screen Printing	Dye Transfer	Dye Direct	
☐			

NOTE: All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty

Soyang Technologies Co., (Soyang Headquarters)

West 19th FL, Yongtong
Information plaza, No. 141
Huancheng Bei Road, Hangzhou
City, Zhejiang PR., China.

www.soyang.net

P. 0086-571-28918690

F. 0086-571-28918695

Soyang Haining Factory

No.36 Jinniu Road, Jianshan District, Haining City, Zhejiang PR, China.

Soyang Hangzhou Factory

No.1199 Gongyuan Xi Rd, Fuyang, Hangzhou City, Zhejiang, PR,
China

Soyang Europe Ltd

Calder House Metcalf
Drive
Altham Industrial estate
Altham Lancashire BB5 5TU UK

www.soyang.co.uk

P. 0044 (0) 161 765 3400

F. 0044 (0) 1282 772982